

HIGH-TEMP SERIES

SEALTITE® HCX EXTREME TEMPERATURE FLEXIBLE CONDUIT



SPECIFICATIONS

- Galvanized steel core with liquid-tight TPE jacket
- Color: Black
- Temp. range: Static installations -76°F to +302°F (-60°C to +150°C). Dynamic installations at atmospheric pressure rated for -76°F to +221°F (-60°C to +105°C)
- UV (sunlight) resistant
- Extra corrosion resistant
- Oil resistant

DESCRIPTION

- Flexible metal core liquid-tight conduit
- Designed for extreme temperature applications where superior resistance to temperature ranges is required. (-76°F to +302°F)
- Available standard in black
- Uses standard liquid-tight connectors for easy installation

APPLICATIONS

- Extreme duty applications
- Extreme high or low temperature requirements
- Applications where no approvals are required



Square-Locked Design with cord packing 3/8" - 1-1/4"

Interlocked Design 1-1/2" - 2"



Trade Size (mm)	Item ID	Std. Pkg. ft	Inside Diameter		Outside Diameter		Bend Radius	Weight lbs/cft
			Min	Max	Min	Max		
3/8" (12)	39102	100	0.485	0.505	0.690	0.710	2.0	21
1/2" (16)	39112	100	0.620	0.640	0.820	0.840	2.5	25
3/4" (21)	39122	100	0.815	0.835	1.030	1.050	3.0	39
1" (27)	39131	100	1.030	1.055	1.290	1.315	4.0	51
1-1/4" (35)	39141	50	1.370	1.395	1.635	1.660	4.5	66
1-1/2" (41)	39151	50	1.575	1.600	1.865	1.900	5.5	104
2" (53)	39161	50	2.020	2.045	2.340	2.375	7.0	136

FITTINGS FINDER



PAGE 33-34



PAGE 34-35



PAGE 37-38